


TYPICAL PROJECT PARAMETERS



UNITS _01 ARE MIRRORED COPIES OF UNITS _04
UNITS _02 ARE MIRRORED COPIES OF UNITS _03
LEVELS 3,4, & 5 ARE GENERALLY THE SAME

GENERAL NOTES 3 (FLOOR PLANS)

- ALL DIMENSIONS IN FLOOR PLANS ARE TO ROUGH FACE OF MASONRY WALL, FLOOR, CEILING OR ELEMENT UNLESS OTHERWISE NOTED BY "F.F." FOR FINISHED FACE. GRID SETTING-OUT DIMENSIONS ARE HIGHLIGHTED IN BLUE.
- Typical wall construction are 8" masonry blocks (7.5" nom) unless otherwise noted. Allowances shall be made for the thickness of finishes and fittings as required.
- Walls are to be placed on center of grid lines.
- All masonry and framed walls are to be constructed within a maximum of 1/8" tolerance of specified dimensions.
- All exterior surfaces exposed to rainfall shall have waterproofing additive in their various build-up applications unless otherwise noted.
- All exterior floor finished surfaces shall be of non-slip finish.
- Field verify all dimensions - typical for all drawings.
- In the event of a discrepancy between architectural and consultant drawings, notify architect immediately prior to commencing work - typical for all drawings.
- All penetrations in fire rated floors and walls must be sealed with appropriate firestop system.
- All walls with sound attenuation blankets are to have acoustical sealant at top and bottom and at all wall penetrations.

Window Schedule (Per Sheet)

Type Mark	Width	Height	Count
W1	2' - 0"	4' - 0"	6
W2	2' - 0"	9' - 0"	2
W3	2' - 0"	9' - 0"	6
W4	3' - 4"	3' - 0"	2
W5	3' - 6"	9' - 0"	10
W6	4' - 3 1/4"	9' - 0"	4
W10	3' - 2 3/4"	9' - 0"	2

Grand total: 32

Door Schedule (per sheet)

Type Mark	Width	Height	Count
DT-1	2' - 9"	7' - 0"	5
DT-2	2' - 11"	7' - 0"	1
DT-4.2	3' - 0"	8' - 0"	2
DT-5	3' - 0"	8' - 0"	7
DT-13	<varies>	<varies>	5
DT-37	6' - 0"	6' - 10"	1

Grand total: 21

ABBREVIATIONS

ABM	ABOVE BENCH MARK
A.F.F.	ABOVE FINISHED FLOOR
LVL	LEVEL
CWP	COLD WATER POINT
HWP	HOT WATER POINT

WALL TYPE LEGEND

- 12" CONCRETE BLOCK WALL (11 1/2" NOM. THICKNESS)
- 8" CONCRETE BLOCK WALL (7 1/2" NOM. THICKNESS)
- 6" CONCRETE BLOCK WALL (5 1/2" NOM. THICKNESS)
- 5 1/2" METAL STUD WALL
- 3 1/2" METAL STUD WALL

Keynote Legend.

Key Value	Keynote Text
FE-33	STAINLESS STEEL POOL HANDRAIL
FE-95	YOKU SH, SAUNA + HAMMAM WITH CANALETTO WALNUT AND TRAVERTINO DARK FINISHES
WP-07	SLOT DRAIN MADE BY CUTTING A CHANNEL INTO THE FLOOR SLAB, PLACING A ROUND PVC TUBE AND TILING OVER IT WITH A 1/2" GAP TO ALLOW WATER TO DRAIN

